

gofanco®

PRO-HD20split2P

1x2 HDMI2.0 splitter with EDID management

User's Guide

gofanco®

Thank you for choosing gofanco



1. Introduction

The PRO-HD20split2P is one input and two output 4K HDMI distribution Amplifier, and support the upmost HDR/4K2K@60 4:4:4 8bits and high definition audio format.

2. Specifications

Item	Description
Role of usage	1x2 Distribution Amplifier
HDMI compliance	HDMI 2.0a
HDCP compliance	HDCP 2.2 / 1.4
Video bandwidth	Single-link 600MHz [18Gbps]
Video support	HDR 4K2K@60(4:2:0 10bits) / 4K2K@60 (4:4:4 8bits)
Audio support	DTS-HD Master Audio, Dolby TrueHD Dolby Digital, LPCM, DVD-Audio, DTS, SACD, MPCM
Input	1x HDMI
Output	2x HDMI
Power supply	5V 1A DC

3. Package Contents

- 1x PRO-HD20split2P
- 1x DC 5V wall wart
- 1x User Manual

4. Features

- HDMI 2.0a compliant
- Supports 4K2K@60 4:4:4 8bits
- Supports HDR, which is 4K2K@60 4:2:0 10bits
- HDCP 2.2 and 1.4 compliant
- Wide frequency range: 25MHz~600MHz
- Video bandwidth: 18Gbps
- Four selections of built-in EDID mode

5. Panel Description



- HDMI OUT 1-2:** Connect to HDMI Displays
- Signal LED:** Output 1-2 signal LED indicator
- Push Button:** Select EDID Mode
- LED Indicator of EDID Mode :**

Color	EDID
Red	Ultra HD(4K2K@60) – 8/10/12bit 3D HDR video & 7.1ch audio
Blue	Ultra HD(4K2K@60) – 8/10/12bit 3D HDR video & 2ch audio
Green	Auto EDID analysis learning mode
Yellow	EDID learning mode

- HDMI IN:** Connect to a HDMI input source
- Micro USB:** Connect to the +5V DC 1A power supply unit